(19) World Intellectual Property Organization

International Bureau





(43) International Publication Date 13 October 2005 (13.10.2005)

PCT

(10) International Publication Number WO 2005/096389 A1

(51) International Patent Classification⁷: **H01L 29/78**, 29/06, 21/336

(21) International Application Number:

PCT/IB2005/051056

(22) International Filing Date: 29 March 2005 (29.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 0407363.1 31 Ma

31 March 2004 (31.03.2004) GB

(71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(71) Applicant and

(72) Inventor: HIJZEN, Erwin, A. [NL/BE]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).


- (72) Inventors; and
- (75) Inventors/Applicants (for US only): ROCHEFORT,

Christelle [FR/BE]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB). MEUNIER-BEILLARD, Philippe [FR/BE]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).

- (74) Agents: WILLIAMSON, Paul, L. et al.; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill Surrey RH1 5HA (GB).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: TRENCH SEMICONDUCTOR DEVICE AND METHOD OF MANUFACTURING IT



(57) Abstract: A RESURF type semiconductor device is manufactured having a drift region (4) over a drain region (2). Trenches (8) are formed through openings in mask (6). A trench insulating layer (12) is deposited on the sidewalls and base of the trenches followed by an overetching step to remove the trench insulating layer (10) from the base of the trenches as well as the top of the sidewalls of the trenches adjacent to the first major surface leaving exposed silicon at the top of the sidewalls of the trench and the base of the trenches. Silicon is selectively grown plugging the trenches with silicon plug (18) leaving void (20).



WO 2005/096389 A1



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

 before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.